

## Worldwide Distributors

### China

#### Pinnacle Scientific Corporation

Tel: +86-571 88 22 51 51  
Fax: +86-571 88 22 52 52

sales@psci.cn  
www.psci.cn

### France

#### Photon Lines

Tel.: +33-130 08 99 00  
Fax: +33-130 08 99 09

infos@photonlines.com  
www.photonlines.fr

### Italy

#### LOT-Oriel Italia

Tel: +39-226 82 21 04  
Fax: +39-226 82 50 07

info@lot-oriel.it  
www.lot-oriel.it

### Japan

#### Japan Laser Corp.

Tel.: +81-352 85 08 61  
Fax: +81-352 85 08 60

lase@japanlaser.jp  
www.japanlaser.jp

### Korea

#### DongWoo Optron Co., Ltd.

Tel.: +82-317 65 03 00  
Fax: +82-317 65 02 22

optron@optron.co.kr  
www.optron.co.kr

### Spain

#### LASER Technology S.L.

Tel.: +34-937 50 01 21  
Fax: +34-937 50 03 23

josecochon@laser-technology.com  
www.laser-technology.com

### Singapore/Malaysia

#### PhotonTech Pte Ltd

Tel.: +65 67 49 90 31  
Fax: +65 62 33 91 71

csales@photonitech.com  
www.photonitech.com

### Taiwan

#### Tayhwa Technology Co. Ltd.

Tel: +88-62 23 56 97 37  
Fax: +88-62 23 56 96 59

tayhwa@tayhwa.com.tw  
www.tayhwa.com.tw

### Turkey

#### MITRA ANONIM SIRKETI

Tel.: +90-21 23 47 47 40  
Fax: +90-21 23 47 47 45

omerbozoglu@mitra.com.tr  
teknofil@mitra.com.tr  
www.mitra.com.tr

### UK

#### Photon Lines Ltd

Tel.: +44-12 95 72 42 25  
Fax: +44-12 95 72 42 26

info-uk@photonlines.com  
www.photonlines.com

### USA

#### Market Tech, Inc.

Tel.: +1-80 03 26 57 14  
Fax: +1-83 14 61 11 36

info@markettechinc.net  
www.markettechinc.net

### Israel


#### Militram

Tel.: +97-299 58 18 60  
Fax: +97-299 57 43 83

militram@militram.com  
www.militram.com



# Narrow Bandwidth DFB Laser Diode Modules



narrow linewidth  
high coherence length




Omicron-Laserage Laserprodukte GmbH  
Raiffeisenstrasse 5e  
63110 Rodgau, Germany  
Tel: +49-61 06-82 24-0  
Fax: +49-61 06-82 24-10  
www.omicron-laser.de  
mail@omicron-laser.de

## DFB Laser Diode Modules

Omicron's Photon-Series lasers offer high performance in all applications where narrow linewidth, stable wavelength and high coherence length is needed.

The **Redphoton® DFB**, "**D**istributed **F**eed**B**ack" laser systems offer narrow linewidth (<2MHz), high output power and optional tunability. The integrated DFB laser diodes are using Bragg gratings, integrated into the active region of the semiconductor, to provide single-frequency operation and high coherence (coherence length up to 250m). The optionally fibre coupled **Redphoton®** DFB laser modules, which are available in a wide range of IR wavelengths are ideal light sources for applications like RAMAN spectroscopy or THz generation, alkaline spectroscopy, gas detection and many others.

Like all Photon-Series laser diode modules they are based on the Omicron modular principle which offers a huge variety of options like direct fibre coupling, focussing and collimation optics, optical isolators, shutters, electro-optical monitoring and many more.



Specifications CWA.L.NB-Models

	Redphoton® CWA.L.NB
Wavelengths & Powers (other wavelengths and powers on request)	<b>Single-Mode:</b> 760nm / 40mW 763nm / 50mW 773nm / 75mW 780nm / 80mW 784nm / 100mW 785nm / 150mW 852nm / 150mW 923nm / 100mW 937nm / 100mW 976nm / 150mW 1060nm / 150mW
Beam diameter (other diameters on request)	1.25mm (1/e <sup>2</sup> ) +/- 0.25mm
Beam quality M <sup>2</sup>	< 1.2
Astigmatism (corrected)	< 0.2*ZR
Beam ellipticity	< 1.1:1
Optical bandwidth	< 10 MHz (2 MHz typical)
Polarisation	> 100:1 vertical
Power stability	< 0.5% / h
Noise 0Hz-100MHz	< 0.5% peak <-> peak
Modulation speed	Analog: 100Hz Digital: 10kHz
Supply voltage	24VDC, 2 Amp.
Features	Safety- interlock LCD-working-hours display Remote-connector
Options	LDM.COL - collimator objective LDM.FOC - customized focussing objective LDM.AAC - <b>Automatic Aging Compensation</b> LDM.FASY.XXX - fibre coupling unit LDM.24VPSU - world wide power supply